


Fassung 1ST (nur DN32)/2ST/4SP/2TE/3TE




Pressfassung 4030, für Schlauch EN 853-1ST(nur DN32) DIN 20022, EN 853-2ST, EN 856-4SP DIN 20023 für Außenschälung, EN 854-2TE und 3TE DIN 20021 für Nichtschälung

Ferrules 4030, for hose EN 853-1ST(only DN32) DIN 20022, EN 853-2ST, EN 856-4SP DIN 20023 for external skive, EN 854-2TE and 3TE DIN 20021 for non-skive

DN	A / mm	B / mm	C / mm	L1 / mm	L2 / mm	Art.Nr.
6	11,0	22,0	15,5	34,0	2,5	4030DN06
8	12,1	23,0	17,2	31,0	2,5	4030DN08
10	14,2	26,0	19,5	38,0	2,5	4030DN10
12	18,5	30,0	22,2	40,0	2,5	4030DN12
16	21,6	33,6	26,4	40,0	2,5	4030DN16
20	24,6	39,0	30,2	50,0	3,0	4030DN20
25	30,9	45,5	37,3	60,0	3,7	4030DN25
32	38,8	58,0	46,8	70,0	4,0	4030DN32
40	44,2	65,0	53,7	73,0	4,3	4030DN40
50	57,3	78,0	66,6	80,0	4,3	4030DN50

Fassung 2TE/3TE



Pressfassung 4040 (4010 nur DN06), für Schlauch nach EN 855 2TE und 3TE für Nichtschälung

Ferrules 4040 (4010 only DN06), for hose EN 855 2TE and 3TE for non-skive

DN	A / mm	B / mm	C / mm	L1 / mm	L2 / mm	Art.Nr.
6	11,3	21,0	15,7	31,0	2,5	4010DN06
8	13,0	22,3	17,2	31,0	2,5	4040DN08
10	14,2	24,0	19,2	33,0	2,5	4040DN10
12	17,8	28,0	23,0	36,0	2,5	4040DN12
16	21,8	33,0	26,9	38,0	2,5	4040DN16
20	24,6	36,0	29,9	44,0	3,0	4040DN20
25	30,8	43,0	37,2	52,0	3,7	4040DN25
32	37,7	49,0	43,5	60,0	4,0	4040DN32