



**AGR-F**

Pressnippel AGR-F, flachdichtend, Außengewinde BSPP

Pressnipple AGR-F, flat sealing, male thread BSPP

DN	A	B / mm	C / mm	L1 / mm	L2 / mm	S1	Art.Nr.
6	G1/4	6.7	3.9	58.8	28.8	19	4715DN06
8	G1/2	8.0	5.4	63.9	33.9	27	4715DN08G04
10	G3/8	9.6	6.5	63.7	30.4	22	4715DN10
10	G1/2	9.6	6.5	67.2	33.9	27	4715DN10G04
12	G3/8	12.8	9.5	64.2	30.7	19	4715DN12G03
12	G1/2	12.8	9.5	69.9	34.6	27	4715DN12
16	G3/4	16.0	12.6	75.5	37.0	27	4715DN16
16	G1	16.0	12.6	79.6	41.3	41	4715DN16G08
20	G3/4	19.1	14.8	83.9	38.1	32	4715DN20
25	G1	25.9	20.0	99.0	43.8	36	4715DN25
32	G1 1/4	32.5	26.0	106.3	46.5	50	4715DN32
40	G1 1/2	38.9	31.0	118.5	50.8	50	4715DN40
50	G2	51.6	40.0	135.3	60.3	70	4715DN50

AGR-D

Pressnippel AGR-D, mit 60° Konus und Dichtkante Form A, Außengewinde BSPP

Pressnipple AGR-D, sealing cone 60° and sealing edge form A, male thread BSPP

DN	A	B / mm	C / mm	L1 / mm	L2 / mm	S1	Art.Nr.
6	G1/8	6.7	3.9	53.3	23.3	14	4720DN06G01
6	G1/4	6.7	3.9	58.8	28.8	19	4720DN06
6	G3/8	6.7	3.9	60.3	30.3	22	4720DN06G03
8	G1/4	8.0	5.4	58.9	28.9	19	4720DN08
8	G3/8	8.0	5.4	60.4	30.4	22	4720DN08G03
8	G1/2	8.0	5.4	63.9	33.9	27	4720DN08G04
10	G1/4	9.6	6.5	62.2	28.9	19	4720DN10G02
10	G3/8	9.6	6.5	63.7	30.4	22	4720DN10
10	G1/2	9.6	6.5	67.2	33.9	27	4720DN10G04
12	G3/8	12.8	9.5	66.6	31.3	22	4720DN12G03
12	G1/2	12.8	9.5	69.9	34.6	27	4720DN12
12	G3/4	12.8	9.5	72.6	37.3	32	4720DN12G06
16	G1/2	16.0	12.6	72.8	34.3	27	4720DN16G04
16	G3/4	16.0	12.6	75.9	37.6	32	4720DN16
20	G3/4	19.1	14.8	83.9	38.1	32	4720DN20
20	G1	19.1	14.8	87.9	42.1	41	4720DN20G08
25	G1	25.9	20.0	98.3	43.3	41	4720DN25
25	G1 1/4	25.9	20.0	100.3	45.3	50	4720DN25G10
32	G1	32.5	26.0	104.0	44.2	41	4720DN32G08
32	G1 1/4	32.5	26.0	106.3	46.5	50	4720DN32
40	G1 1/2	38.9	31.0	120.3	52.8	55	4720DN40
50	G2	51.6	40.0	135.3	60.3	70	4720DN50