


## CEL




Pressnippel CEL, mit 24° Konus, Schneidringanschluss, leichte Reihe

Pressnipple CEL, cone 24° for cutting ring connection, light duty series

DN	Rohr	A	B / mm	C / mm	L1 / mm	L2 / mm	S1	Art.Nr.
6	6	M12x1,5	6.7	3.9	53.5	23.5	14	4300DN06M12
6	8	M14x1,5	6.7	3.9	53.5	23.5	14	4300DN06
6	10	M16x1,5	6.7	3.9	55.5	25.5	17	4300DN06M16
8	10	M16x1,5	8.0	5.4	54.6	24.6	17	4300DN08
8	12	M18x1,5	8.0	5.4	55.7	25.7	19	4300DN08M18
10	10	M16x1,5	9.6	6.5	57.9	24.6	17	4300DN10M16
10	12	M18x1,5	9.6	6.5	59.0	25.7	19	4300DN10
10	15	M22x1,5	9.6	6.5	61.0	27.7	22	4300DN10M22
12	12	M18x1,5	12.8	9.5	62.0	26.7	19	4300DN12M18
12	15	M22x1,5	12.8	9.5	63.6	28.3	22	4300DN12
16	18	M26x1,5	16.0	12.6	67.6	29.3	27	4300DN16
20	22	M30x2	19.1	14.8	78.6	32.8	30	4300DN20
25	28	M36x2	25.9	20.0	89.5	34.5	36	4300DN25
32	35	M45x2	32.5	26.0	99.5	39.7	46	4300DN32
40	42	M52x2	38.9	31.0	110.0	42.5	55	4300DN40

## CES



Pressnippel CES, mit 24° Konus, Schneidringanschluss, schwere Reihe

Pressnipple CES, with 24° cone for cutting ring connection, heavy duty series

DN	Rohr	A	B / mm	C / mm	L1 / mm	L2 / mm	S1	Art.Nr.
6	8	M16x1,5	6.7	3.9	55.5	25.5	17	4400DN06M16
6	10	M18x1,5	6.7	3.9	56.5	26.5	19	4400DN06
8	10	M18x1,5	8.0	5.4	56.6	26.6	19	4400DN08M18
8	12	M20x1,5	8.0	5.4	57.6	27.6	22	4400DN08
10	12	M20x1,5	9.6	6.5	61.0	27.7	22	4400DN10M20
10	14	M22x1,5	9.6	6.5	62.9	29.6	22	4400DN10
10	16	M24x1,5	9.6	6.5	62.9	29.6	24	4400DN10M24
12	16	M24x1,5	12.8	9.5	65.6	30.3	24	4400DN12
16	20	M30x2	16.0	12.6	72.6	34.3	30	4400DN16
20	20	M30x2	19.1	14.8	80.6	34.8	30	4400DN20M30
20	25	M36x2	19.1	14.8	83.6	37.8	36	4400DN20
25	25	M36x2	25.9	20.0	93.5	38.5	36	4400DN25M36
25	30	M42x2	25.9	20.0	97.5	42.5	46	4400DN25
32	38	M52x2	32.5	26.0	107.5	47.7	55	4400DN32