




DKOL 45°




Pressnippel DKOL 45°, Dichtkegel mit 24° Konus und O-Ring, leichte Reihe, Dichtkopf metrisch

Pressnipple DKOL 45°, sealing cone 24° with o-ring, sealing head thread metric, light duty series

DN	Rohr	A	B / mm	C / mm	L1 / mm	L2 / mm	L3 / mm	S1	Art.Nr.
6	6	M12x1,5	6.7	3.9	67.8	37.8	15.0	14	4101DN06M12
6	8	M14x1,5	6.7	3.9	67.8	37.8	15.0	17	4101DN06
6	10	M16x1,5	6.7	3.9	71.0	41.0	17.0	19	4101DN06M16
8	10	M16x1,5	8.0	5.4	70.0	40.0	16.5	19	4101DN08
8	12	M18x1,5	8.0	5.4	70.8	40.8	16.5	22	4101DN08M18
10	12	M18x1,5	9.6	6.5	75.6	42.3	16.0	22	4101DN10
10	15	M22x1,5	9.6	6.5	74.5	41.2	17.5	27	4101DN10M22
12	15	M22x1,5	12.8	9.5	82.0	46.7	21.0	27	4101DN12
16	18	M26x1,5	16.0	12.6	91.0	52.7	22.0	32	4101DN16
20	22	M30x2	19.1	14.8	115.0	69.2	26.0	36	4101DN20
25	28	M36x2	25.9	20.0	133.0	78.0	30.0	41	4101DN25
32	35	M45x2	32.5	26.0	156.0	96.2	39.0	50	4101DN32
40	42	M52x2	38.9	31.0	176.0	108.5	41.0	60	4101DN40

DKOL 90°



Pressnippel DKOL 90°, Dichtkegel mit 24° Konus und O-Ring, leichte Reihe, Dichtkopf metrisch

Pressnipple DKOL 90°, sealing cone 24° with o-ring, sealing head thread metric, light duty series

DN	Rohr	A	B / mm	C / mm	L1 / mm	L2 / mm	L3 / mm	S1	Art.Nr.
6	6	M12x1,5	6.7	3.9	59.0	29.0	33.5	14	4102DN06M12
6	8	M14x1,5	6.7	3.9	59.0	29.0	33.5	17	4102DN06
6	10	M16x1,5	6.7	3.9	57.5	27.5	31.5	19	4102DN06M16
6	12	M18x1,5	6.7	3.9	58.0	28.0	35.8	22	4102DN06M18
8	10	M16x1,5	8.0	5.4	60.0	30.0	33.0	19	4102DN08
8	12	M18x1,5	8.0	5.4	58.0	28.0	35.8	22	4102DN08M18
10	10	M16x1,5	9.6	6.5	69.0	35.5	38.5	19	4102DN10M16
10	12	M18x1,5	9.6	6.5	72.0	38.7	36.0	22	4102DN10
10	15	M22x1,5	9.6	6.5	70.5	37.2	38.0	27	4102DN10M22
12	12	M18x1,5	12.8	9.5	74.5	39.2	44.0	22	4102DN12M18
12	15	M22x1,5	12.8	9.5	76.0	40.5	43.0	27	4102DN12
12	18	M26x1,5	12.8	9.5	79.0	43.7	44.5	32	4102DN12M26
16	18	M26x1,5	16.0	12.6	85.0	46.5	52.0	32	4102DN16
20	22	M30x2	19.1	14.8	102.0	56.2	55.0	36	4102DN20
25	28	M36x2	25.9	20.0	123.0	68.0	70.0	41	4102DN25
32	35	M45x2	32.5	26.0	148.0	88.2	84.0	50	4102DN32
40	42	M52x2	38.9	31.0	189.0	121.5	102.0	60	4102DN40